



Код/артикул изделия	H1, м	H2, м	L, м	L1, м	L2, м	G1, гр.	G2, гр.	Вес, кг.	Закладная в грунт	Закладная стилобат	Крышка декоративная
PR120.2Z-3-15	3	2	1,8	0,94	0,87	15	15	73	ZF-01-1,50-0133	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-3-45	3	2	1,75	0,9	0,85	45	45	73			
PR120.2Z-3-90	3	2	1,85	0,99	0,9	90	90	73			
PR120.2Z-3,5-15	3,5	2,5	1,8	0,94	0,87	15	15	77	ZF-01-1,50-0133	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-3,5-45	3,5	2,5	1,75	0,9	0,85	45	45	77			
PR120.2Z-3,5-90	3,5	2,5	1,85	0,99	0,9	90	90	77			
PR120.2Z-4-15	4	3	1,8	0,94	0,87	15	15	82	ZF-01-1,50-0133	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-4-45	4	3	1,75	0,9	0,85	45	45	82			
PR120.2Z-4-90	4	3	1,85	0,99	0,9	90	90	82			
PR120.2Z-4,5-15	4,5	3,5	1,8	0,94	0,87	15	15	86	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-4,5-45	4,5	3,5	1,75	0,9	0,85	45	45	86			
PR120.2Z-4,5-90	4,5	3,5	1,85	0,99	0,9	90	90	86			
PR120.2Z-5-15	5	4	1,8	0,94	0,87	15	15	91	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-5-45	5	4	1,75	0,9	0,85	45	45	91			
PR120.2Z-5-90	5	4	1,85	0,99	0,9	90	90	91			
PR120.2Z-5,5-15	5,5	4,5	1,8	0,94	0,87	15	15	96	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-5,5-45	5,5	4,5	1,75	0,9	0,85	45	45	96			
PR120.2Z-5,5-90	5,5	4,5	1,85	0,99	0,9	90	90	96			
PR120.2Z-6-15	6	5	1,8	0,94	0,87	15	15	102	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-6-45	6	5	1,75	0,9	0,85	45	45	102			
PR120.2Z-6-90	6	5	1,85	0,99	0,9	90	90	102			
PR120.2Z-6,5-15	6,5	5,5	1,8	0,94	0,87	15	15	112	ZF-02-2,00-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-6,5-45	6,5	5,5	1,75	0,9	0,85	45	45	112			
PR120.2Z-6,5-90	6,5	5,5	1,85	0,99	0,9	90	90	112			
PR120.2Z-7-15	7	6	1,8	0,94	0,87	15	15	121	ZF-02-2,00-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-7-45	7	6	1,75	0,9	0,85	45	45	121			
PR120.2Z-7-90	7	6	1,85	0,99	0,9	90	90	121			
PR120.2Z-7,5-15	7,5	6,5	1,8	0,94	0,87	15	15	133	ZF-02-2,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-7,5-45	7,5	6,5	1,75	0,9	0,85	45	45	133			
PR120.2Z-7,5-90	7,5	6,5	1,85	0,99	0,9	90	90	133			
PR120.2Z-8-15	8	7	1,8	0,94	0,87	15	15	142	ZF-02-2,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZK-02-135-1212 KZF-06-135-1212 KZP-01-118-1212
PR120.2Z-8-45	8	7	1,75	0,9	0,85	45	45	142			
PR120.2Z-8-90	8	7	1,85	0,99	0,9	90	90	142			

Напряжение в сети, В	Мощность, Вт.	Индекс CRI	Цветовая температура, К	Световая отдача, лм/Вт.
230В AC (50 Гц)	50/110/220	70..90	2700-6000	150