



Код/артикул изделия	H, м	L, м	L1, м	G, гр	Вес, кг	Закладная в грунт	Закладная столба	Крышка декоративная
PR108.2-3-15	3	0,7	1,25	15	36	ZF-01-1,50-0108	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-05-100-108
PR108.2-3-45	3	0,7	1,16	45	36			
PR108.2-3-90	3	0,7	1,32	90	36			
PR108.2-3,5-15	3,5	0,7	1,25	15	40	ZF-01-1,50-0108	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-05-100-108
PR108.2-3,5-45	3,5	0,7	1,16	45	40			
PR108.2-3,5-90	3,5	0,7	1,32	90	40			
PR108.2-4-15	4	0,7	1,25	15	45	ZF-01-1,50-0108	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-05-100-108
PR108.2-4-45	4	0,7	1,16	45	45			
PR108.2-4-90	4	0,7	1,32	90	45			
PR108.2-4,5-15	4,5	0,7	1,25	15	49	ZF-01-1,50-0108	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-05-100-108
PR108.2-4,5-45	4,5	0,7	1,16	45	49			
PR108.2-4,5-90	4,5	0,7	1,32	90	49			
PR108.2-5-15	5	0,7	1,25	15	54	ZF-01-1,50-0133	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-05-100-108
PR108.2-5-45	5	0,7	1,16	45	54			
PR108.2-5-90	5	0,7	1,32	90	54			
PR108.2-5,5-15	5,5	0,7	1,25	15	58	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-05-100-108
PR108.2-5,5-45	5,5	0,7	1,16	45	58			
PR108.2-5,5-90	5,5	0,7	1,32	90	58			
PR108.2-6-15	6	0,7	1,25	15	65	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-05-100-108
PR108.2-6-45	6	0,7	1,16	45	65			
PR108.2-6-90	6	0,7	1,32	90	65			

Напряжение в сети, В	Мощность, Вт	Индекс CRI	Цветовая температура, К	Световая отдача, лм/Вт
230В AC (50 Гц)	50/110/220	70..90	2700-6000	150