



Код/артикул изделия	H, м	L, м	L1, м	G, гр	Вес, кг	Закладная в грунт	Закладная столбчат	Крышка декоративная
PR133.2-3-15	3	0,8	1,6	15	60	ZF-01-1,50-0133	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-3-45	3	0,76	1,56	45	60			
PR133.2-3-90	3	0,83	1,63	90	60			
PR133.2-3,5-15	3,5	0,8	1,6	15	67	ZF-01-1,50-0133	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-3,5-45	3,5	0,76	1,56	45	67			
PR133.2-3,5-90	3,5	0,83	1,63	90	67			
PR133.2-4-15	4	0,8	1,6	15	74	ZF-01-1,50-0133	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-4-45	4	0,76	1,56	45	74			
PR133.2-4-90	4	0,83	1,63	90	74			
PR133.2-4,5-15	4,5	0,8	1,6	15	81	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-4,5-45	4,5	0,76	1,56	45	81			
PR133.2-4,5-90	4,5	0,83	1,63	90	81			
PR133.2-5-15	5	0,8	1,6	15	88	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-5-45	5	0,76	1,56	45	88			
PR133.2-5-90	5	0,83	1,63	90	88			
PR133.2-5,5-15	5,5	0,8	1,6	15	95	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-5,5-45	5,5	0,76	1,56	45	95			
PR133.2-5,5-90	5,5	0,83	1,63	90	95			
PR133.2-6-15	6	0,8	1,6	15	102	ZF-01-1,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-6-45	6	0,76	1,56	45	102			
PR133.2-6-90	6	0,83	1,63	90	102			
PR133.2-6,5-15	6,5	0,8	1,6	15	109	ZF-02-2,00-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-6,5-45	6,5	0,76	1,56	45	109			
PR133.2-6,5-90	6,5	0,83	1,63	90	109			
PR133.2-7-15	7	0,8	1,6	15	116	ZF-02-2,00-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-7-45	7	0,76	1,56	45	116			
PR133.2-7-90	7	0,83	1,63	90	116			
PR133.2-7,5-15	7,5	0,8	1,6	15	123	ZF-02-2,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-7,5-45	7,5	0,76	1,56	45	123			
PR133.2-7,5-90	7,5	0,83	1,63	90	123			
PR133.2-8-15	8	0,8	1,6	15	132	ZF-02-2,50-0159	ZBF-51-0,30-0001 ZAF-51-0,30-0002	KZF-06-135-135
PR133.2-8-45	8	0,76	1,56	45	132			
PR133.2-8-90	8	0,83	1,63	90	132			

Напряжение в сети, В	Мощность, Вт	Индекс CRI	Цветовая температура, К	Световая отдача, лм/Вт
230В AC (50 Гц)	50/110/220	70..90	2700-6000	150